

GP-ATLAS[®]

WORLD CLASS



The choice of **GREATER POWER** for Quality You know you can Trust!

Manufactured by **ATLASBX**, one of the top Korean manufacturers in automotive industry with export to over 130 countries.

Enhanced with World Class quality certified by **German TUV**, a world renowned stringent German Standards Authority.

Benefits of **GP-ATLAS** Fully Sealed Maintenance Free Battery:-

- Superior quality batteries at affordable prices
- Uniquely constructed with special protective tissue for each positive and negative plates to prevent shedding of active materials and to ensure longer life span
- Superb protection against road vibrations / shocks, which will help reduce premature failure
- Extra long lasting due to slower self discharge rate

BATTERY SPECIFICATIONS

AUTOMOTIVE		DIMENSION (mm)				AH@	CCA@	RC	LAYOUT	TERMINAL	HOLD-DOWN	WET WEIGHT
JIS TYPE	NEW JIS	L	W	H	TH	20HR	-18°C (SAE)	MINS				(KG)
NS40Z/L	40B19R/L	187	127	200	220	35	335	56	1/2	B	-	10.00
NS60/L	50B24R/L	234	127	200	220	45	400	75	1/2	A/B	-	12.00
NS50/L	48D26R/L	257	172	200	220	50	450	85	1/2	A	-	15.90
NS02/L	55D26R/L	257	172	200	220	60	550	100	1/2	A	-	17.20
55D23/L	55D23R/L	230	172	200	220	60	550	100	1/2	A	-	16.50
NS70/L	65D26R/L	257	172	200	220	65	580	120	1/2	A	-	17.50
NX110-5/L	80D26R/L	257	172	200	220	70	600	125	1/2	A	-	18.00
N70/L	70D31R/L	302	172	200	220	70	600	130	1/2	A	-	19.50
N70Z/L	75D31R/L	302	172	200	220	75	630	140	1/2	A	-	20.30
NX120-7/L	95D31R/L	302	172	200	220	80	670	160	1/2	A	-	21.50
DIN TYPE	DIN CODE											
DIN 55*	55530	242	175	175	175	55	500	90	1	A	1	14.70
DIN 66*	56618	277	175	175	175	66	580	110	1	A	1	17.70
DIN 85*	58515	354	175	175	175	85	780	160	1	A	2	22.10
DIN 88*	58815	354	175	175	175	88	800	160	1	A	2	22.10
DIN 100	60038	354	175	190	190	100	850	170	1	A	2	23.80

* All DIN sizes are low version



- 1 **Excellent Handle Design**
 - Easy battery replacement
- 2 **Magic-Eye Indicator**
 - Easy to check state of charging
- 3 **Special Sealed Cover**
 - Prevent acid leakage
 - Minimize gassing
 - Flame arrestor prevents sparks / flames from external sources
- 4 **Advanced Center Lug & Cast-On-Strap**
 - Resistance to vibration
 - High cranking performance
- 5 **Integrated Computer Design & Reinforced Container**
 - Protect the battery from vibration & impact

- 6 **New Wrought High-Tin-Calcium Grid**
 - Resistance to grid-corrosion & overcharging
 - Minimal gassing & water-loss
 - Minimize self-discharge & thermal-runaway



- 7 **Upgrade Pasted-Cured Plate**
 - Resistance to vibration
 - Improved life-cycle




- 8 **Special Tissue**
 - New special material instead of common pulp tissue increases durability of plate by reducing aging-rate of active material




- 9 **Low Electric Resistance Envelop Separator**
 - High cranking performance
 - Prevent internal short-circuit between positive & negative plates

TECHNICAL INFORMATION

LAYOUT



HOLD-DOWN



TERMINAL

	A (STANDARD)	B (SMALL)	C (TOP POST)
Positive Terminal			
Negative Terminal			



GRAND PRIX

ATLAS®



GERMAN CERTIFIED



Calcium-Calcium MF Battery

MADE IN KOREA

FULLY SEALED MAINTENANCE FREE BATTERY

The choice of **GREATER POWER** for Quality You know you can Trust!

- Manufactured by **ATLASBX**, one of the top Korea manufacturers in automotive industry with export to over 130 countries.
- Enhanced with World Class quality certified by **German TUV**, a world renowned stringent German Standards Authority.
- Benefits of **GRAND PRIX - ATLAS** Fully Sealed Maintenance Free Battery:-
 - Superior quality batteries at affordable prices
 - Uniquely constructed with special protective tissue for each positive and negative plates to prevent shedding of active materials and to ensure longer life span
 - Superb protection against road vibrations / shocks, which will help reduce premature failure
 - Extra long lasting due to slower self discharge rate

BATTERY SPECIFICATIONS

AUTOMOTIVE		DIMENSION (mm)				AH@ 20HR	CCA@ -18°C (SAE)	RC MINS	LAYOUT	TERMINAL	HOLD-DOWN	WET WEIGHT (KG)
JIS TYPE	NEW JIS	L	W	H	TH							
NS40Z/L	40B19R/L	187	127	200	220	35	335	56	1/2	B	-	10.00
NS60/L	50B24R/L	234	127	200	220	45	400	75	1/2	A/B	-	12.00
N50/L	48D26R/L	257	172	200	220	50	450	85	1/2	A	-	15.90
N50Z/L	55D26R/L	257	172	200	220	60	550	100	1/2	A	-	17.20
55D23/L	55D23R/L	230	172	200	220	60	550	100	1/2	A	-	16.50
NS70/L	65D26R/L	257	172	200	220	65	580	120	1/2	A	-	17.50
NX110-5/L	80D26R/L	257	172	200	220	70	600	125	1/2	A	-	18.00
N70/L	70D31R/L	302	172	200	220	70	600	130	1/2	A	-	19.50
N70Z/L	75D31R/L	302	172	200	220	75	630	140	1/2	A	-	20.30
NX120-7/L	95D31R/L	302	172	200	220	80	670	160	1/2	A	-	21.50
DIN TYPE	DIN CODE											
DIN 55*	55530	242	175	175	175	55	500	90	1	A	1	14.70
DIN 66*	56618	277	175	175	175	66	580	110	1	A	1	17.70
DIN 85*	58515	354	175	175	175	85	780	160	1	A	2	22.10
DIN 88*	58815	354	175	175	175	88	800	160	1	A	2	22.10
DIN 100	60038	354	175	190	190	100	850	170	1	A	2	23.80


* All DIN sizes are low version

TECHNICAL INFORMATION

LAYOUT



HOLD-DOWN



TERMINAL

	A (STANDARD)	B (SMALL)	C (TOP POST)
Positive Terminal			
Negative Terminal			




- Excellent Handle Design**
 - Easy battery replacement
- Magic-Eye Indicator**
 - Easy to check state of charging
- Special Sealed Cover**
 - Prevent acid leakage
 - Minimize gassing
 - Flame arrestor prevents sparks / flames from external sources
- Advanced Center Lug & Cast-On-Strap**
 - Resistance to vibration
 - High cranking performance
- Integrated Computer Design & Reinforced Container**
 - Protect the battery from vibration & impact

- New Wrought High-Tin-Calcium Grid**
 - Resistance to grid-corrosion & overcharging
 - Minimal gassing & water-loss
 - Minimize self-discharge & thermal-runaway



- Upgrade Pasted-Cured Plate**
 - Resistance to vibration
 - Improved life-cycle



- Special Tissue**
 - New special material instead of common pulp tissue increases durability of plate by reducing aging-rate of active material



- Low Electric Resistance Envelop Separator**
 - High cranking performance
 - Prevent internal short-circuit between positive & negative plates

Authorised Dealer:

